


Specifications

SBA-L projection audio system for SMART Board® interactive whiteboard systems

Model SBA-L

Physical specifications

Size (one speaker)	5 1/8" W × 24" H × 4" D (13 cm × 61 cm × 10.2 cm)
Weight (both speakers)	11 lb. 14 oz. (5.4 kg)
With brackets added	13 lb. 11 oz. (6.2 kg)
Shipping size	12 3/4" W × 8" H × 26 1/2" D (32.4 cm × 20.3 cm × 67.3 cm)
Shipping weight	18 lb. (8.2 kg)



All dimensions +/- 1/8" (0.3 cm). All weights +/- 2 lb. (0.9 kg).

Standard features

Mounting brackets	Mount the speakers directly to your SMART Board® 800ix, 800i5, 800i4, 600ix, 600i5 or 600i4 series interactive whiteboard system.
Color	Dark gray and silver
Connectivity	Dual RCA receptacles on the bottom of the right (active) speaker connect to the projector.
Frequency range	50 Hz to 20 kHz ± 6 dB
Output	14 W RMS both channels driven simultaneously. The audio system provides a comfortable listening volume in rooms up to 1,000 square feet (93 square meters) in size, with a 30-person capacity (subject to room acoustics).

Connection panel (right speaker)	Polarized Molex® connector and 16 AWG wire with sufficient slack to discreetly route wire behind your interactive whiteboard or along the floor
Dual RCA	Connects to the projector
Power	Powered barrel connector (15V DC, 4A), positive center
Power requirements	Switching power supply (100V–240V AC, 50 Hz–60 Hz, 1.5A) and a 14' 9 1/8" (4.5 m) country-specific power cord (15V DC, 4000 mA, 60 VA, positive tip)
Environmental compliance	EU RoHS, China EIP, EU WEEE
Regulatory certification	CE, CSA/UL
Warranty	One-year limited equipment warranty

Operating specifications

41°F to 95°F (5°C to 35°C) with up to 80% humidity, non-condensing



CAUTION

If the speakers are very cold, allow them to warm to room temperature before operation.

SMART order number

SBA-L SBA-L projection audio system for SMART Board 800ix, 800i5, 800i4, 600ix, 600i5 and 600i4 series interactive whiteboard systems

Physical dimensions

