

Specifications

SMART kappiQ Pro

SMART kapp iQ Pro[™] 55

Overview

SMART kapp iQ Pro™ combines SMART kapp iQ's simple yet powerful whiteboard experience with the advanced collaboration capabilities of SMART Meeting Pro® software to provide a solution that adapts seamlessly to any meeting. Get started quickly with the natural walk up and use experience of the SMART kapp iQ: just pick up a pen and write. You can write notes in black or red ink using the provided pens and erase notes with the pens' erasers or with your palm or fist. Use the SMART kapp app to connect a Bluetooth®-enabled mobile device to capture and share your work. When you connect your mobile device, you can invite others to simultaneously view and contribute to your notes from their own web-enabled devices

Switch to SMART Meeting Pro with a press of a button to use more advanced collaboration tools and enhance meeting productivity. SMART Meeting Pro software's touch-enabled whiteboarding features, unbound workspace, superior




See smartkapp.com for more information about SMART kapp iQ Pro.



Dimensions and weights¹

Dimensions



Weight

107 lb. (48.4 kg)

Shipping dimensions (including pallet)

59 7/8" × 11" × 44 1/4" (152 cm × 28 cm × 112.5 cm)

Shipping weight

146 lb. (66.4 kg)

 $^{^1} All \ dimensions \pm 1/8"$ (0.3 cm). All weights $\pm \ 2 \ lb.$ (0.9 kg).

Hardware

Interaction

Touch technology DViT® (Digital Vision Touch) technology

Multitouch capabilities 4 touches

Object awareness Behavior adjusts automatically depending on the tool or object being used, whether it's a pen,

finger, eraser or palm.

Pen ID™ Two people can write independently and simultaneously, using different colored ink.

Display

Type LED

Aspect ratio 16:9

Optimal resolution 3840 × 2160 at 30 Hz (HDMI® input only)

HDMI

Horizontal frequency 244–280 kHz (analog and digital)

Vertical frequency 24–120 Hz

Contrast ratio (typical) 1400:1

Brightness (typical) 280–360 cd/m²

Pixel pitch 0.315 mm

Gamut 72% of NTSC

Viewing angle 178°

Response time 8 ms

Wireless technology Bluetooth 4.0 dual mode (backwards compatible with Bluetooth 2.1 + EDR)

Capture options Establish a Bluetooth wireless connection with a supported mobile device (see below) by

scanning the interactive flat panel's unique QR code

Presence detection Presence detection sensor on the bottom frame

Audio 10 W integrated side-firing speakers (×2)

Noise level 35 dBA

Included cables and accessories 8^{\prime} (2.4 m) country-specific power cable

16' 5" (5 m) USB cable 20' 8" (6.3 m) HDMI cable CAT 5 USB extender

Pen (×2)

Included hardware AM30 appliance

I/O extension module²

 $^{^2\}mbox{Only}$ one hardware module can be installed at a time

Mounting holes For a standard VESA® 400 mm × 400 mm mounting plate

11 1/8" (28.2 cm) from the bottom of the interactive flat panel

Mounting bracket depth Minimum depth of 15/8" (4.2 cm) for all components on the back of the interactive flat panel to

clear the wall

Connectors

Side Side connector panel: AM30 appliance:

 $\begin{array}{lll} \text{USB 2.0 Type-B} & \text{USB 3.0 Type-A (\times 2)} \\ \text{HDMI 1.4 in} & \text{USB 2.0 Type-B (\times 2)}^3 \\ \text{Stereo 3.5 mm out} & \text{I/O extension module:} \\ \text{RS-232 in} & \text{USB 2.0 Type-B} \end{array}$

HDMI 1.4 in

Bottom USB 2.0 Type-A

Back AC power inlet

Installation requirements

Interactive flat panel See the SMART kapp iQ Pro interactive flat panels administrator's guide

SMART kapp app

Apple devices iOS 8.1 or later operating system software

50 MB of storage iPhone 4S or later

Third generation iPad or later First generation iPad mini or later Fifth generation iPod touch or later

Android™ devices Android 4.4.4 (KitKat) or later operating system

50 MB of storage (internal or SD card)

1024 MB of RAM

720p or better screen resolution

Bluetooth 2.1 + EDR

3 megapixel or better rear-facing camera (recommended)

SMART kapp viewer

Mobile Safari for iOS 8.1 or later operating system software

Chrome™ for Android 39.0.2171.93 or later

Desktop Internet Explorer® 10 or later

Chrome 39.0.2171.95 or later Firefox® 34.0.5 or later Safari 8.0 or later

³For service use only

Room computers and guest laptops

General requirements See smarttech.com/SMARTMeetingProReleaseNotes

4K UHD Graphics card that can support 3840 × 2160 resolution at 30 Hz and that has 1 GB DDR 5 memory

See kb.smarttech.com/?q=15546

Storage and operating requirements

Power requirements 90V to 240V AC, 50 Hz to 60 Hz

Power consumption at 77°F (25°C)

Standby mode 25 W

Normal operating 122 W

Maximum operating 134 W

Operating temperature 41–95°F (5–35°C)

Storage temperature -4-140°F (-20-60°C)

Humidity 5–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification

With AM30 appliance UL (U.S./Canada), FCC, IC, CE Mark, RCM Mark

With I/O extension

module

UL (U.S./Canada), FCC, IC, CE Mark, RCM Mark, CCC, EAC, VCCI, SPRING, KC Mark

Environmental compliance

European Union REACH, RoHS, WEEE and Packaging

U.S. Packaging and Conflict Minerals

Purchasing information

Order numbers

KAPPIQ-PRO-55 SMART kapp iQ Pro 55 interactive flat panel, including one SMART Meeting Pro software room

license and 25 SMART Meeting Pro software personal licenses

Optional accessories

WM-SBID-501 Fixed wall mount for SMART interactive flat panels

Other See smarttech.com/businessaccessories

Warranty Three-year limited equipment warranty

SMART advanced support

Designed to limit downtime and optimize return on investment, SMART Support Services provide peace of mind and maximize the performance of your SMART solution. These offerings give you access to expert support, guaranteed response times and advance hardware replacement. Three service offerings are available: Basic, Elite and Platinum. For more information, see smarttech.com/services.

smarttech.com/support smarttech.com/contactsupport

© 2015–2016 SMART Technologies ULC. All rights reserved. SMART kapp, SMART kapp iQ, SMART Meeting Pro, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. All third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. 04/2016.