

Specifications

SMART Room System[™] for Microsoft® Lync® for large rooms

Model SRS-LYNC-L

Overview


The SMART Room System™ for Microsoft® Lync® for large rooms features two SMART Board® 8070i-G4 interactive flat panels, a tabletop console, a high-definition camera, table microphones and speakers.

Using the installed Lync Room System software, you can start a meeting and connect with other individuals or meeting rooms with a single tap on the console or one of the interactive flat panels. You can write or draw on an interactive flat panel using the whiteboard feature, present a Microsoft PowerPoint® slide show, connect a laptop to share its screen and share your content with connected individuals and meeting rooms in real time.



See smarttech.com/smartroom for more information on this product.

Dimensions and weights¹



1

¹All dimensions \pm 0.3cm (1/8"). All weights \pm 0.9kg (2lb)

 ${\sf SMART\ Room\ System\ for\ Microsoft\ Lync\ for\ large\ rooms-Model\ SRS-LYNC-L}$

	Weight	Dispatch weight	Dispatch dimensions
Interactive flat panel (×2)	93kg (205 lb)	122.7kg (271 lb)	180cm x 125cm x 100cm (70 7/8" × 49 1/4" × 39 3/8")
WM-SBID-501 wall mount (×2)	10.9kg 24lb	14kg (31 lb)	117cm x 32cm x 28.1cm (46" × 12 1/2" × 11")
Speakers	7kg (15 lb)	9.1 kg (20lb)	96cm x 39.5cm x 18.8cm (37 3/4" × 15 1/2" × 7 3/8")
System components	6.2kg (14 lb)	10.8kg (24lb)	49.5cm x 45.7cm x 57.2cm (19 1/2" × 18" × 22 1/2")
Total	221kg (487 lb)	312kg (688 lb) ²	

Hardware

Included hardware

SBID 8070i-G4	SMART Board 8070i-G4 interactive flat panel (×2)		
AM70-L	Lync appliance		
XTM	I/O extension module		
CP311	Console		
CAM301	Camera		
MIC500	Table microphone (×2)		
MIX500	Audio processor		
CSR500	Speakers		
WM-SBID-501	Wall mount for installing an interactive flat panel on a wall (×2)		
Included cables			
For interactive flat panels	2.4m (8') IEC 60320 C13 to country-specific power (×2) HDMI USB		
For console	6.3m (20' 8") HDMI, VGA and USB 2.4m (8') IEC 60320 C13 to country-specific power AC/DC converter		
For camera	USB and power		
For table microphones and audio processor	9m (30') interactive flat panel to table 4m (13') microphone to microphone		
For laptop ³	9.3m (30' 6") harness (HDMI and VGA)		
Recommended diameter for conduit	4.5cm (1 3/4")		

2

²Including the pallet

³Laptop not included

Interactive flat panels

Touch technology DViT® (Digital Vision Touch) technology

Screen size (diagonal)

178cm (70")

Aspect ratio

16:9

Optimal resolution

1920 × 1080 at 60 Hz

Horizontal frequency

54-69.75 kHz (analogue and digital)

Vertical frequency

48-62 Hz

Contrast ratio (typical)

4000:1

Brightness (typical)

180-250 cd/m²

Pixel pitch

0.807 mm

Lync appliance

Processor

2.3 GHz Intel® Core™ i7 with HD 4000 graphics chipset

RAM

Dual-channel 8 GB DDR3

Console

Screen size

29.5cm (11 5/8")

(diagonal)
Aspect ratio

16:9

Resolution

1366 × 768

Brightness

250 cd/m²

Camera

Features Digital pan, tilt and zoom (DPTZ)

Automatic white balance

Automatic exposure and power line frequency detection

Manual lens tilt adjustment Internal privacy shutter Video recording indicator

Aspect ratio 16:9

Resolution

1920 × 1080

(maximum)

Frame rate (typical) 30 frames per second (at ≥ 200 lx)

Field of view

109° (full) 98° (horizontal)

Depth of field

1-10m (3'-33')

Signal-to-noise ratio

33 dB at ≥ 50 lx 36 dB at ≥ 200 lx

(minimum)

42 dB

Dynamic range

(minimum)

SPECIFICATIONS

SMART Room System for Microsoft Lync for large rooms – Model SRS-LYNC-L

Table microphones

Features Mute button and indicator

> 4m (13') cable between microphones Daisy-chain up to five microphones

Local speaker audio

level

60-65 dBA measured at 0.5m (20")

Speakers

Total harmonic < 1% average distortion

< 3% maximum 80-10 kHz

Frequency response \pm 6 dB, 80-10 kHz

Nominal volume 76 dBSPL

Audio

Echo cancellation > 45 dB at nominal receive output level

Software

Lync Room System

software

See lync.microsoft.com

Storage and operating requirements

Room system power (excluding console)

Power requirements 9.5A at 100V to 4A at 240V AC, 50 Hz to 60 Hz

Power consumption

950 W

at 25°C (77°F)

Console power

< 12 W (supplied using the 12 V AC/DC converter) Normal power

consumption

< 0.6 W

Standby power

consumption

5-35°C (41-95°F)

Operating temperature

Storage temperature -40-60°C (-40-140°F)

Humidity 85% relative humidity, non-condensing

Certification and compliance

Regulatory certification⁴ UL (US and Canada), FCC, IC, C-Tick, NOM, CU, CB, VCCI, KC, CCC, PSB, BIS, PSE, KCC

⁴As applicable to the components

Environmental compliance

China EIP

European Union REACH, RoHS, WEEE, Battery and Packaging

US Packaging and Conflict Minerals

Purchasing information

Order number

SRS-LYNC-L SMART Room System for Lync for large rooms

Optional accessories

MIC500 Add-on microphone

WSK-L Wall stand kit for large rooms, including two wall stands for transferring some of the weight of

the interactive flat panels to the floor and one cable track

Warranty

Two-year warranty Interactive flat panels

Camera

Lync appliance I/O extension module

Console

One-year warranty Speakers

Wall mounts

No warranty Cables, pens, batteries and other items that can be purchased from parts.smarttech.com

smarttech.com/support smarttech.com/contactsupport

© 2013 SMART Technologies ULC. All rights reserved. SMART Room System, SMART Board, DViT, smarttech, the SMART logo and all SMART taglines are trade-marks or registered trade-marks of SMART Technologies ULC in the US and/or other countries. Microsoft, Lync and PowerPoint are either registered trade-marks or trade-marks of Microsoft Corporation in the US and/or other countries. All other third-party product and company names may be trade-marks of their respective owners. This product and/or use thereof covered by one or more of the following US patents. www.smarttech.com/patents. Contents are subject to change without notice. 08/2013.